

FTB

FTB ANTI-GRAFFITI TYPE 2

ART NR 70.101

BIODEGRADABLE ANTI-GRAFFITI COATING SYSTEM ON A WAX BASIS

DESCRIPTION

FTB ANTI-GRAFFITI TYPE 2 IS A BIODEGRADABLE ANTI-GRAFFITI COATING SYSTEM ON A WAX BASIS. FTB ANTI-GRAFFITI TYPE 2 WORKS IN THE SAME MANNER AS THE DEFENCE SYSTEM OF PLANTS AND FRUITS. THEY HAVE A SMALL WAX COATING LAYER WHICH PROTECTS THEM AGAINST RAIN AND OTHER MICRO-ORGANISMS.

CHARACTERISTICS

- 1 COMPONENT
- HARMLESS FOR PEOPLE
- VAPOUR PERMEABLE
- INVISIBLE AFTER SECURING
- BIODEGRADABLE
- UV-RESISTANT FOR A MINIMUM OF 3 YEARS
- RESISTANT AGAINST ACID RAIN
- VERY EASY TO PROCESS

METHOD OF WORKING

PREPARATION OF THE SUPPORT:

THE SURFACES TO PROTECT MUST BE DRY AND CLEAN FOR THE APPLICATION OF FTB ANTI-GRAFFITI TYPE 2. WE RECOMMEND TO WAIT 6 WEEKS FOR THE APPLICATION OF THE GRAFFITI PROTECTION ON NEW CONCRETE AND WALLS.

TREATMENT:

DEPENDING ON THE SUPPORT FTB ANTIFRAFFITI TYPE 2 CAN AND MAY BE APPLIED WITH A BRUSH, ROLLER OR GRUN (AIRLESS OR OTHER).

WILL BE APPLIED IN MINIMUM 2 LAYERS, ON CONCRETE PREFERABLY 3 LAYERS.

FTB ANTI-GRAFFITI TYPE 2 WILL BE BEST APPLIED AT A TEMPERATURE BETWEEN, 5°C AND 40°C.

WHEN SPILLING ON GLASS, WOOD, ETC. THE STAINS CAN BE REMOVED EASILY WITH HOT WATER.

NOT START THE WORK IF IT COULD RAIN. THE PRODUCT MUST SECURE AT LEAST 4 HOURS AFTER THE APPLICATION. AFTER THE SECURING OF THE FIRST LAYER (APPROX. 5 HOURS), THE SECOND LAYER MAY BE APPLIED. FTB ANTI-GRAFFITI 2 MAY ALSO BE USED ON A PAINTED SURFACE.

REMOVAL OF THE GRAFFITI:

GRAFFITI CAN BE REMOVED WITH A HIGH PRESSURE CLEANER AND HOT WATER. PRESSURE 80 BAR AND A TEMPERATURE OF APPROX. 85° TO 90°C.

AFTER THIS CLEANING SESSION AGAIN TWO LAYERS OF FTB ANTI-GRAFFITI TYPE 2 MUST BE APPLIED.

■ **CONSUMPTION**

DEPENDING ON THE SUPPORT: 8 TO 15 M² / 1 LITRE FTB ANTI-GRAFFITI TYPE 2.

■ **CONDITIONING**

5 LTR – 25 LTR

■ **EPILOGUE**

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.