

FTB

# FTB CEM CLEAN

ART NR 90.400

CLEANSING AGENT TO REMOVE "VEIL" AND RESTS OF CEMENT

## DESCRIPTION

FTB CEM CLEAN IS A REMOVER TO REMOVE ORGANIC DIRT, CEMENT- AND PLASTER "VEIL" FROM FIRED TILES AND BRICKS.

## APPLICATION

FTB CEM CLEAN IS READY TO USE AND WILL NOT BE DILUTED. CONSUMPTION: 0,5 TO 1 LITRE/M<sup>2</sup>, DEPENDING ON THE STRUCTURE OF THE OBJECT TO BE CLEANED. FTB CEM CLEAN IS APPLIED WITH A WIDE PAINTER'S BRUSH OR WITH A DRENCHED SPONGE.

POLISH THE SURFACE TO BE CLEANED, WITH A ROTATING MOVEMENT, IN ORDER TO DISSOLVE THE POLLUTION.

WHEN THE FOAMING ACTION HAS STOPPED, THE ACTIVE ACTION IS FINISHED AND ABUNDANTLY CLEANING WITH WATER SHOULD BE DONE.

THICKER CEMENT-RESTS MUST BE TREATED SEVERAL TIMES.

THE REMAINING PRODUCT CAN BE DRAINED AFTER NEUTRALISATION.

TOOLS OF STAINLESS STEEL CAN TURN COLOUR. ZINC AND ALUMINIUM AND OTHER LESS PRECIOUS METALS ARE TO BE PROTECTED.

## CLEANING OF THE MATERIAL

WITH WATER OR A NEUTRALIZER

## CONDITIONING

10 LTR

## STORAGE TIME

1 YEAR IN CLOSED CONDITIONING AND FROST-FREE.

## ■ PRECAUTIONS

---

AVOID CONTACT WITH THE SKIN. CAREFULLY WASH HANDS WITH WATER AND SOAP BEFORE SMOKING OR EATING. ENSURE A GOOD VENTILATION DURING THE APPLICATION OF THE PRODUCT. DON'T BREATHE IN SPRAY-MIST. IN CASE OF CONTACT WITH THE EYES, RINSE THE OPENED EYE IMMEDIATELY DURING 15 MINUTES WITH WATER AND CONSULT A DOCTOR.

## ■ EPILOGUE

---

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.