

FTB

FTB DECAP 100

ART NR 90.200

PAINT STRIPPER, READY FOR USE, IN PASTE FORM TO REMOVE PAINT LAYERS, GLUE RESTS AND CERTAIN SYNTHETIC MATERIALS

DESCRIPTION

FTB DECAP 100 IS A READY FOR USE PASTE WITH A GENTLY SPREADABLE QUALITY. EXTREMELY SUITABLE TO REMOVE OLD PAINT LAYERS, GLUE RESTS AND CERTAIN SYNTHETIC MATERIALS.

METHOD OF WORKING

APPLY FTB DECAP 100 WITH A BRUSH OR A ROLLER IN A 2 TO 3 MM THICK LAYER. SOAK DURING ABOUT TEN MINUTES. REMOVE THE PLASTIC PAINT REST WITH A FILLING-KNIFE OR A BRUSH. IF NECESSARY, REPEAT THE TREATMENT SEVERAL TIMES. THE ACTION OF FTB DECAP 100 CAN BE EXTENDED BY COVERING THE PASTE WITH A POLYPROPYLENE OR ALUMINIUM FOIL.

CLEANING OF THE MATERIAL

FTB DECAP 100 IS VOLATILE. DRYED RESTS CAN BE REMOVED VERY WELL WITH FRESH FTB DECAP 100.

CHARACTERISTICS

DENSITY:	APPROX. 1,20 KG/DM ³
COLOUR:	LIGHT PINK
ODOUR:	CHARACTERISTIC (ANAESTHETIZING)
VISCOSITY:	PASTY, GENTLY SPREADABLE

CONSUMPTION

DEPENDING ON THE THICKNESS OF THE PAINT

■ **CONDITIONING**

1 KG, 5 KG, 10 KG

■ **STORAGE TIME**

MAXIMUM 1 YEAR IN CLOSED CONDITIONING AND FROST-FREE.

■ **PRECAUTIONS**

AVOID CONTACT WITH THE SKIN. CAREFULLY WASH HANDS WITH WATER AND SOAP BEFORE SMOKING OR EATING.

ENSURE A GOOD VENTILATION, DO NOT INHALE THE MIST, IN CASE OF CONTACT WITH THE EYES, RINSE IMMEDIATELY THE OPENED EYE WITH WATER DURING 15 MINUTES AND CONSULT A DOCTOR.

THE DAMP IS HEAVIER THAN AIR. FTB DECAP 100 ATTACKS MANY SYNTHETIC MATERIALS.

■ **EPILOGUE**

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.