

FTB

# FTB FAÇADE CREAM

ART NR 40.030

IMPREGNATION CREAM SUITABLE FOR THE HYDROFUGATION OF MINERAL SUPPORTS ON A BASIS OF SILOXANE/SILANE

## DESCRIPTION

FTB FAÇADE CREAM IS AN IMPREGNATION CREAM SUITABLE FOR THE HYDROFUGATION OF MINERAL SUPPORTS.

## COMPOSITION

FTB FAÇADE CREAM IS AN IMPREGNATION CREAM ON A BASIS OF SILANE/SILOXANE.

## APPLICATION

FTB FAÇADE CREAM IS A SPECIAL PRODUCT FOR THE HYDROFUGATION OF BRICKS, CLINKERS, LIME SAND STONE, STUCCO, PLASTER LAYERS AND NATURAL STONE. SO THAT THE TREATED SURFACE IS OPTIMALLY PROTECTED AGAINST WATER AND THE ABSORPTION OF DETRIMENTAL SUBSTANCES AND FROST/THAW SALT DAMAGE.

## METHOD OF WORKING

### PREPARATION OF THE SUPPORT:

THE SUPPORT MUST BE IN GOOD CONDITION: TEARS, BAD JOINTS, BAD CONNECTIONS MUST BE TREATED IN ADVANCE. THE SUPPORT MUST BE CLEAN AND AS DRY AS POSSIBLE. IF NECESSARY CLEAN THE FRONTAGE CAREFULLY AND REMOVE ALL THE RESTS OF THE FRONTAGE CLEANING PRODUCTS BECAUSE THIS CAN INFLUENCE BADLY THE ACTION OF THE CREAM. COVER THE ADJACENT PARTS, THAT DON'T NEED TO BE TREATED (P.EX. GLASS, PLANTS, PAINT, ETC).

**REMARK:** NON-POROUS SUPPORTS (P.EX. MARBLE) MAY NOT BE TREATED WITH FTB FAÇADE CREAM.

### TREATMENT:

APPLY FTB FAÇADE CREAM UNDILUTED ON THE MINERAL SUPPORT BY AIRLESS SPRAYING IN THE WANTED LAYER THICKNESS. SMALLER SURFACES CAN BE TREATED WITH A BRUSH OR A ROLLER.

DEPENDING ON THE ABSORPTION OF THE SUPPORT ONE OR TWO MAYERS ARE APPLIED, ALSO ON VERTICAL PARTS AND ABOVE THE HEAD, WITHOUT THE MATERIAL FLOWING DOWN FROM THE SUPPORT OR LEAKING.

**REMARK:** IN CASE THE SUPPORT SHOWS SALTS, AN ANALYSIS SHOULD BE CARRIED OUT BEFORE DOING THE HYDROFUGATION.

## CLEANING OF THE MATERIAL

---

WITH WATER OR WHITE SPIRIT.

## CHARACTERISTICS

---

FORM:	PASTY
COLOUR:	MILKY WHITE
ODOUR:	ALMOST ODOURLESS
DENSITY AT 20°C:	0.9 KG/DM <sup>3</sup>
SOLUBILITY IN WATER:	MISCIBLE
SECURING TIME:	APPROX. 1 HOUR AFTER TREATMENT RAIN-RESISTANT
FLASH POINT:	APPROX. 69°C
PERCENTAGE ACTIVE SUBSTANCES:	APPROX. 40 M-%

## CONSUMPTION

---

CA. 0,2 LITER/M<sup>2</sup>

## CONDITIONING

---

5 L - 20 L

## STORAGE TIME

---

MAXIMUM 1 YEAR IN CLOSED CONDITIONING AND FROST-FREE.

## PRECAUTIONS

---

- KEEP OUT OF REACH OF CHILDREN AND KEEP AWAY FROM FOOD AND DRINKS
- WEAR SUITABLE PROTECTIVE CLOTHING, GLOVES AND A PROTECTION FOR THE EYES AND THE FACE
- ONLY USE IN WELL VENTILATED AREAS
- KEEP DISTANCE FROM IGNITION SOURCES - DON'T SMOKE

## EPILOGUE

---

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.