

FTB

# FTB FLOORPROTECT AQ

**ART NR 70.102**

WATER BASED PROTECTIVE COATING AGAINST PENETRATING WATER, OIL AND OTHER GREASE STAINS

## DESCRIPTION

FTB FLOOR PROTECT AQ IS A WATER AND OIL REPELLENT PRODUCT WITH ANTI-GRAFFITI PROPERTIES: IT IS WATER BASED AND IT PROTECTS THE SUPPORT AGAINST PENETRATING WATER, OIL AND OTHER GREASE STAINS.

FTB FLOOR PROTECT AQ HAS AN EFFICIENCY OF MORE THAN 10 YEARS AT NORMAL USE.

FTB FLOOR PROTECT AQ PENETRATES THE SURFACE THROUGH CAPILLARITY AND PREVENTS PENETRATION OF WATER AND GREASES IN THE MATERIALS. THE PROTECTION IS MICRO POROUS, SO THE SURFACE CAN BREATHE AND WATER MIST CAN PASS.

THE PRODUCT IS COLOURLESS, ODOURLESS AND DOESN'T CHANGE THE ORIGINAL ASPECT OF THE MATERIALS.

COLOURLESS LIQUID : ACRYLATE POLYMER IN WATER PHASE. **NON TOXIC - NOT CORROSIVE. NON FLAMMABLE.**

## ADVANTAGES

LONG TERM PROTECTION AGAINST WATER AND GREASE STAINS. DECREASES THE STICKING OF CHEWING-GUM TO THE FLOOR. PREVENTS FROST DAMAGE.

EASY TO APPLY, WITHOUT DILUTION, ON UNPROTECTED SUPPORTS. ALLOWS EXCHANGE OF GASES AND ALLOWS THE MATERIALS TO BREATHE. MAKES THE MAINTENANCE EASIER AND REDUCES THE MAINTENANCE COSTS.

FTB FLOOR PROTECT AQ PROTECTS ALL POROUS MATERIALS FROM THE BUILDING, CAN BE APPLIED ON HORIZONTAL AS WELL AS VERTICAL SURFACES, INDOORS OR OUTDOORS, IDEAL FOR THE PREVENTIVE TREATMENT OF FLOORS.

## METHOD OF WORKING

---

FTB FLOOR PROTECT AQ IS APPLIED WITHOUT ANY EXTRA PROTECTION FOR MEN OR ENVIRONMENT BY AIRLESS ROLLER OR BRUSH.

SURFACE CAN BE WASHED WITH NEUTRAL DETERGENT.

THE MATERIAL IS CLEANED WITH WATER.

BEFORE APPLICATION THE PH OF THE SURFACE IS CHECKED TO SEE IF IT IS NEUTRAL ( $6 < \text{PH} < 8$ )

NEUTRALISE THE SURFACE FIRST IF ACID OR ALKALINE CLEANING PRODUCTS WERE USED.

APPLY IN ONE OR TWO LAYERS TILL THE SUPPORT IS SATURATED. DO NOT APPLY ON FRESH CONCRETE.

DO NOT APPLY WITH RAINY WEATHER OR FROST.

DRYING TIME 24 HOURS. MAXIMUM EFFICIENCY AFTER 7 DAYS.

## CLEANING OF THE MATERIAL

---

WITH CLEAN WATER.

## CONSUMPTION

---

FROM 2 TO 15 M<sup>2</sup>/LITER DEPENDING ON THE POROSITY OF THE SURPPORT.

## CONDITIONING

---

1 LTR, 5 LTR

## STORAGE TIME

---

1 YEAR IN CLOSED CONDITIONING AND FROST-FREE.

## EPILOGUE

---

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.