

FTB

FTB TOP

ART NR 10.201 – 10.960

2-COMPONENT ORGANIC DISPERSION FOR THE DECORATIVE COATING OF FRONTAGE ELEMENTS WITH THE COLOUR AND THE STRUCTURE OF NATURAL STONE.

DESCRIPTION

FTB TOP IS A DECORATIVE COATING OF FRONTAGE ELEMENTS WITH THE COLOUR AND THE STRUCTURE OF NATURAL STONE.

APPLICATION

FTB TOP IS A DECORATIVE COATING OF FRONTAGE ELEMENTS WITH THE COLOUR AND THE STRUCTURE OF NATURAL STONE.

COMPOSITION

* COMPONENT A: FTB TOP POWDER.

* COMPONENT B: FTB TOP LIQUID, COMPOSED OF ACRYLATE POLYMER AND WATER

METHOD OF WORKING

PREPARATION OF THE SUPPORT:

THE SUPPORT MUST BE DUST- AND FAT-FREE AND IN ADVANCE APPLIED WITH FTB TOP LIQUID.

TREATMENT:

FTB TOP - POWDER IS MIXED WITH THE FTB TOP - LIQUID AND APPLIED ON THE WET FTB TOP LIQUID LAYER WITH A BRUSH OR A HAWK.

FTB TOP IS APPLIED IN 2 LAYERS WITH A MAXIMUM THICKNESS OF 5 MM.

AFTER HARDENING (\pm 24 HOURS) THE SURFACE IS SLIGHTLY SCAURED WITH SANDPAPER OR AN ELECTRIC SANDING MACHINE

CLEANING OF THE MATERIAL

WITH WATER.

CHARACTERISTICS

DENSITY: 1,1 K/L
SECURING TIME: COMPLETE HARDENING AFTER 24 HOURS.

CONSUMPTION

DEPENDING ON THE APPLICATION \pm 500 G/M²

CONDITIONING

FTB TOP - POWDER (ART. NR. 10.201): 20 KG
FTB TOP - LIQUID (ART. NR. 10.960): 10 LITRE

PRECAUTIONS

THERE ARE NO SPECIAL PRECAUTIONS TO TAKE.

EPILOGUE

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.