

FTB

FTB MMA PRIMER

ART NR 110.210

PRIMER FOR FTB MMA SYSTEMS

DESCRIPTION

PRIMER FOR FTB MMA SYSTEMS.

APPLICATION

PRIMER FOR FTB MMA FLOORING SYSTEMS.

- MAKES FTB MMA SYSTEM EASILY TO MAINTAIN AND TO CLEAN.
- FOR A BETTER ADHERENCE OF THE FTB MMA SYSTEM.

COMPOSITION

- ONE SET FTB MMA PRIMER CONTAINS 2 COMPONENTS:
 COMPONENT A: LIQUID PMMA RESIN
 COMPONENT B: CATALYST
- ALL COMPONENTS ARE PREPARED IN THE RIGHT DOSAGE.

METHOD OF WORKING

- MIX THOROUGHLY THE IN THE RIGHT DOSAGE PREPARED COMPONENTS A AND B WITH A SLOWLY TURNING MIXER.
- APPLY FTB MMA PRIMER WITH A BRUSH OR A ROLLER.
- POT-LIFE: ABOUT 15 MINUTES AT 20°C.
- DO NOT SMOKE OR MAKE OPEN FIRE DURING THE APPLICATION !
- FTB MMA PRIMER IS NOT POISONOUS, IT SPREADS A SPECIFIC ODOUR; THE AREA MUST BE VERY WELL VENTILATED.
- CLEAN THE MATERIAL WITH FTB CLEAN 1.

CONDITIONING

3,5 KG, 7 KG



STORAGE TIME

6 MONTHS IN A DRY ENVIRONMENT AND PROTECTED TO DIRECT SUNLIGHT AND FROST-FREE.



EPILOGUE

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.