



# FTB MMA TOPCOAT

ART NR 110.201

TOPCOAT FOR FTB MMA SYSTEMS

## DESCRIPTION

TOPCOAT FOR FTB MMA SYSTEMS.

## APPLICATION

TOPCOAT FOR FTB MMA FLOORING SYSTEMS, FTB MMA TOPCOAT IS ALSO AVAILABLE IN RAL-COLOURS.

- MAKES FTB MMA SYSTEM EASILY TO MAINTAIN AND TO CLEAN.
- FOR A BETTER ADHERENCE OF THE FTB MMA SYSTEM.

## COMPOSITION

- ONE SET FTB MMA TOPCOAT CONTAINS 2 COMPONENTS:  
 COMPONENT A: LIQUID PMMA RESIN  
 COMPONENT B: CATALYST
- ALL COMPONENTS ARE PREPARED IN THE RIGHT DOSAGE.

## METHOD OF WORKING

- MIX THOROUGHLY THE IN THE RIGHT DOSAGE PREPARED COMPONENTS A AND B WITH A SLOWLY TURNING MIXER.
- APPLY FTB MMA TOPCOAT WITH A BRUSH OR A ROLLER.
- POT-LIFE: ABOUT 15 MINUTES AT 20°C.
- DO NOT SMOKE OR MAKE OPEN FIRE DURING THE APPLICATION !
- FTB MMA TOPCOAT IS NOT POISONOUS, IT SPREADS A SPECIFIC ODOUR; THE AREA MUST BE VERY WELL VENTILATED.

## CLEANING OF THE MATERIAL

WITH FTB CLEAN 1.

■ **CONDITIONING**

---

7 KG

■ **STORAGE TIME**

---

6 MONTHS IN A DRY ENVIRONMENT AND PROTECTED TO DIRECT SUNLIGHT AND FROST-FREE.

■ **EPILOGUE**

---

OUR TECHNICAL INFORMATION IS BASED ON OUR OWN EXPERIENCE AND IS GIVEN IN GOOD FAITH. WE GUARANTEE A CONSTANT QUALITY OF OUR PRODUCTS, BUT WE CANNOT ACCEPT ANY RESPONSIBILITY CONCERNING THEIR APPLICATION.